Declaration of Performance

No. HHW - 30





Hördener Holzwerk Landstr.25 76571 Gaggenau Germany

1	Unique identification code of the product-type	Glued laminated timber made of spruce
2	Date of production	The date of production can be taken from
		identification of the product
3	Use of the construction product	Buildings and bridges
4	Manufacturer	Hördener Holzwerk
		Landstr.25
		76571 Gaggenau
		Germany
5	Authorised representative	No authorised representative
6	System of assessment and verification of	System 1
	constancy of performance	
7	Harmonised standard	EN 14080:2013
	Notified body	MPA Stuttgart
8	Declared performance	
	Essential characteristics	Performance
	Essential characteristics Module of elasticity	GL 24 and 28
	Essential characteristics Module of elasticity Bending strength	GL 24 and 28 The allocation of timber delivered to strength classes
	Essential characteristics Module of elasticity Bending strength Compressive strength	GL 24 and 28 The allocation of timber delivered to strength classes can be taken from the delivery note.
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength	GL 24 and 28 The allocation of timber delivered to strength classes can be taken from the delivery note. The respective product dimensions can be found
	Essential characteristics Module of elasticity Bending strength Compressive strength	GL 24 and 28 The allocation of timber delivered to strength classes can be taken from the delivery note.
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength	GL 24 and 28 The allocation of timber delivered to strength classes can be taken from the delivery note. The respective product dimensions can be found in the accompanying documents.
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength	GL 24 and 28 The allocation of timber delivered to strength classes can be taken from the delivery note. The respective product dimensions can be found in the accompanying documents. Widths of 100 mm to 200 mm
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength	GL 24 and 28 The allocation of timber delivered to strength classes can be taken from the delivery note. The respective product dimensions can be found in the accompanying documents. Widths of 100 mm to 200 mm Heights of 100 mm to 440 mm
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength Geometric data	GL 24 and 28 The allocation of timber delivered to strength classes can be taken from the delivery note. The respective product dimensions can be found in the accompanying documents. Widths of 100 mm to 200 mm Heights of 100 mm to 440 mm Lengths up to 15,00 m
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength Geometric data Adhesion as bending strength of finger-joints	GL 24 and 28The allocation of timber delivered to strength classescan be taken from the delivery note.The respective product dimensions can be foundin the accompanying documents.Widths of 100 mm to 200 mmHeights of 100 mm to 440 mmLengths up to 15,00 mPanel lamellar joints in accordance with EN 1194
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength Geometric data Adhesion as bending strength of finger-joints	GL 24 and 28The allocation of timber delivered to strength classescan be taken from the delivery note.The respective product dimensions can be foundin the accompanying documents.Widths of 100 mm to 200 mmHeights of 100 mm to 440 mmLengths up to 15,00 mPanel lamellar joints in accordance with EN 1194Bonded joints in accordance with EN 386Adhesive type I in accordance with EN 301Durability class 4 in accordance with EN 350-2
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength Geometric data Adhesion as bending strength of finger-joints as adhesive joints integrity of surface bonding	GL 24 and 28The allocation of timber delivered to strength classescan be taken from the delivery note.The respective product dimensions can be foundin the accompanying documents.Widths of 100 mm to 200 mmHeights of 100 mm to 440 mmLengths up to 15,00 mPanel lamellar joints in accordance with EN 1194Bonded joints in accordance with EN 386Adhesive type I in accordance with EN 301Durability class 4 in accordance with EN 350-2The usage classes permissible for use should
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength Geometric data Adhesion as bending strength of finger-joints as adhesive joints integrity of surface bonding Natural durability	GL 24 and 28The allocation of timber delivered to strength classescan be taken from the delivery note.The respective product dimensions can be foundin the accompanying documents.Widths of 100 mm to 200 mmHeights of 100 mm to 440 mmLengths up to 15,00 mPanel lamellar joints in accordance with EN 1194Bonded joints in accordance with EN 386Adhesive type I in accordance with EN 301Durability class 4 in accordance with EN 350-2The usage classes permissible for use shouldbe taken from the national regulations
	Essential characteristics Module of elasticity Bending strength Compressive strength Tensile strength Shear strength Geometric data Adhesion as bending strength of finger-joints as adhesive joints integrity of surface bonding	GL 24 and 28The allocation of timber delivered to strength classescan be taken from the delivery note.The respective product dimensions can be foundin the accompanying documents.Widths of 100 mm to 200 mmHeights of 100 mm to 440 mmLengths up to 15,00 mPanel lamellar joints in accordance with EN 1194Bonded joints in accordance with EN 386Adhesive type I in accordance with EN 301Durability class 4 in accordance with EN 350-2The usage classes permissible for use should

Signed for and on behalf of the manufacturer by:

Dominik Strobel, CEO

Gaggenau, 18.08.2015

Place and data of issue

Signature